

HCH-APX6-CHG

Charger Specifications:

Operating Temp: 0°C to 45°C
(32°F to 113°F)
Storage Temp: -20°C to 70°C
(-4°F to 158°F)

Dimensions:
Length: 455.6 mm
Width: 142.9 mm
Height: 101.6 mm
weight: 2466.4 g

Warranty:
Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries

- HIS4037-M(27)
(Battery Only)
- H7144-M(27)
(Battery Only)
- HIS8299-M(40)
- H8299-M(40)
- H8610-Li
- H8610IS-Li
- H9858-M(27)
- H7038-LiP NEOCELL® Battery
- H9858-LiP NEOCELL® Battery
- H8610-LiP NEOCELL® Battery
- H9013-LiP NEOCELL® Battery



- Highest quality cells used.
- Longer cycle life.
- Extremely rugged.
- Rigorous testing.



Trademarks are the sole property of their respective owners.

14.03.28

Six Bay Universal Charger for Motorola® XTS 1500/2500/3000/5000, APX6000/7000, HT1000 and MTS2000 Series Radios

Multi-chemistry charger
Supports Li-Ion, NiCd, NiMH and NEOCELL® Lithium Polymer chemistries.

Internally mounted power supply, small footprint.

Charges mixed fleets in same cup without need for adapter.

Replaces two chargers with one unit.

Made of highly-rugged aerospace grade aluminum housing.

Light-weight, versatile and portable design for desktop operation.



Charges battery alone or while attached to radio.

Hassle-free mounting bracket.

Designed for the appropriate level of operational RF immunity.

Tri-color charging indications:
Charging LED indicates charging status.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1

